IN THE CLAIMS

This listing of claims replaces all prior listings:

1. (Currently Amended) A magnetic recording head for a helical scan type magnetic recording/reproducing apparatus comprising:

a multi-gap recording head formed by laminating "n" recording heads and having "n" recording gaps, said "n" being an integer greater than 2,

wherein,

said "n" recording gaps are wider than a track pitch and partially overlap each other in a <u>cascading</u> pitched manner along a width direction of the recording head so as to record a pattern of juxtaposed tracks; and

a gap for recording the last track among "n" recording gaps of said multi-gap recording head being wider than other gaps.

2. (Currently Amended) A rotary drum unit for a helical scan type magnetic recording/reproducing apparatus comprising:

a recording head;

a reproducing head; and

a unit for transmitting recording and reproduced signals,

wherein,

said recording head comprises a multi-gap recording head formed by laminating "n" recording heads and having "n" recording gaps,

said "n" recording gaps are wider than a track pitch and partially overlap each other in a <u>cascading</u> pitched manner along a width direction of the recording head so as to record a pattern of juxtaposed tracks[[;]], and said "n" being an integer greater than 2, and

a gap for recording the last track among "n" recording gaps of said multi-gap recording head being wider than other gaps.

Response to December 5, 2007 Final Office Action Application No. 10/774,201 Page 3

3. (Previously Presented) The rotary drum unit according to claim 2, further comprising:

two multi-gap reproducing heads, each formed by laminating "n" reproducing heads and having "n" reproducing gaps, are arranged at an angle of 180° to each other.

- 4. (Previously Presented) The rotary drum unit according to claim 2, wherein: the multi-gap reproducing head is formed by laminating "n" recording heads has "2n" reproducing gaps, and is arranged at an angle of 180° to said multi-gap recording head.
- 5. (Currently Amended) A rotary drum unit <u>according to claim 2 capable of</u> recording "n" tracks per rotation, further comprising:

two multi-gap reproducing heads each formed by laminating "n" reproducing heads, and having "n + m" reproducing gaps, and each of the reproducing heads having a head width which is 1/2 of a track width or less,

wherein,

said n being an integer greater than 2 and m being an integer greater than or equal to 1, respectively.

6. (Currently Amended) A rotary drum unit <u>according to claim 2 capable of</u> recording "n" tracks per rotation, <u>further</u> comprising:

a multi-gap reproducing head formed by laminating "2n + m" reproducing heads, and having "2n + m" reproducing gaps, and each of the reproducing heads having a head width which is 1/2 of a track width or less,

wherein,

said n being an integer greater than 2 and m being an integer greater than or equal to 1.

7. (Currently Amended) A magnetic recording method for a helical scan type magnetic recording/reproducing apparatus, said apparatus includes a multi-gap recording head formed by laminating "n" recording heads and having "n" recording gaps, said "n" being an integer greater than 2, said "n" recording gaps are wider than a track pitch and partially overlap

each other in a <u>cascading</u> pitched manner along a width direction of the recording head so as to record a pattern of juxtaposed tracks, and a gap for recording the last one of said tracks among "n" gaps of multi-gap recording head being a wider recording gap than other gaps, said method comprising the step of:

recording said tracks by determining a tape running speed such that a minimum recorded track width can be ensured when said multi-gap recording head overwrites after one rotation of recording completed by said gap.

8. (Previously Presented) A magnetic recording/reproducing method according to claim 7, further comprising the step of:

reproducing signals recorded in the recording step by a multi-gap reproducing head formed by laminating multiple reproducing heads and having a head width which is 1/2 of a track width or less,

wherein,

two multi-gap reproducing heads each having "n" gaps are arranged at an angle of 180° to each other on a rotary drum as said multi-gap reproducing head, and said two multi-gap reproducing heads are switched on said rotary drum to transmit reproduced signals therefrom via a rotary transformer having "n" recording channels and "n" reproducing channels.

9. (Previously Presented) A magnetic recording/reproducing method according to claim 7, further comprising the step of:

reproducing signals recorded by the recording step by a multi-gap reproducing head formed by laminating multiple reproducing heads and having a head width which is 1/2 of a track width or less.

wherein,

a multi-gap reproducing head having "2n" gaps is arranged at an angle of 180° to said multi-gap recording head on a rotary drum as said multi-gap reproducing head; and

said n-channel multi-gap recording head and said multi-gap reproducing head are switched on said rotary drum to transmit reproduced signals from said multi-gap reproducing head via a rotary transformer having "n" recording channels and "n" reproducing channels.

10. (Previously Presented) A magnetic recording/reproducing method according to claim 7, further comprising the step of:

reproducing said signals recorded by the recording step by two multi-gap reproducing heads, each having "n + m" gaps, said "m" being an integer greater than or equal to 1.

11. (Previously Presented) A magnetic recording/reproducing method according to claim 7, further comprising the step of:

reproducing said signals recorded by the recording step by a multi-gap reproducing head having "2n + m" gaps, said "m" being an integer greater than or equal to 1.

12. (Currently Amended) A helical scan type magnetic recording/reproducing apparatus comprising:

a multi-gap recording head formed by laminating "n" recording heads and having "n" recording gaps, said "n" recording gaps are wider than a track pitch and partially overlap each other in a <u>cascading</u> pitched manner along a width direction of the recording head so as to record a pattern of juxtaposed tracks; and

a gap for recording the last track among said "n" recording gaps of said multi-gap recording head being wider than other gaps to obtain a recorded pattern of narrow tracks,

wherein,

said signals are reproduced by a multi-gap reproducing head having "2n + m" gaps, said multi-gap reproducing head formed by laminating (2n + m) reproducing heads, and

said "n" being an integer greater than 2 and "m" being an integer greater than or equal to 1.

13. (Previously Presented) The magnetic recording/reproducing apparatus according to claim 12, further comprising:

Response to December 5, 2007 Final Office Action Application No. 10/774,201 Page 6

two multi-gap reproducing heads each having "n" reproducing gaps are arranged at an angle of 180° to each other on a rotary drum.

14. (Previously Presented) The magnetic recording/reproducing apparatus according to claim 12, further comprising:

a multi-gap reproducing head having "2n" reproducing gaps is arranged at an angle of 180° to said multi-gap recording head.

15. (Currently Amended) A magnetic recording/reproducing apparatus <u>according to</u> <u>claim 12 eapable of recording a pattern of "n" tracks per rotation</u>, <u>further comprising</u>:

two multi-gap reproducing heads each having "n + m" reproducing gaps said multi-gap reproducing head formed by laminating "n + m" reproducing heads, and each of the reproducing heads having a head width which is 1/2 of a track width or less,

wherein,

said "n" being an integer greater than 2 and "m" being an integer greater than or equal to 1.

16. (Currently Amended) A magnetic recording/reproducing apparatus <u>according to</u> <u>claim 12 eapable of recording a pattern of "n" tracks per rotation</u>, <u>further</u>:

a multi-gap reproducing head having "2n + m" reproducing gaps, said multi-gap reproducing head formed by laminating "2n + m" reproducing heads, and each of the reproducing heads having a head width which is 1/2 of a track width or less,

wherein,

said "n" being an integer greater than 2 and "m" being an integer greater than or equal to 1.